

HS ELASTOSEAL PRIMER



SCIENTIFIC WATERPROOFING SOLUTIONS

Aromatic Polyurethane Primer

Description

HS ELASTOSEAL PRIMER is single component polyurethane resin based low viscous highly penetrative primer.

Characteristics

Working Life @ 30 °C, hrs	6 - 7	Surface Dry, @ 30 °C, minutes	35 – 45
Recoating Time, hrs	2	Theoretical Coverage*, m ² / L / coat	4 - 5
DFT in microns	40 - 50		

* Depending upon surface condition.

Application

- Concrete / metal surfaces.

Advantages

- Better adhesion and flexibility.
- Chemical resistance.
- Improved performance over manually prepared concrete surfaces.

Application Methodology

○ Surface Preparation

- Prepare the surface by mechanical grinding or other suitable method.
- Remove dust, flakes, oil, grease or other loose foreign particles by sand blasting, iron brush or compressed air. Remove old painting using surface grinder.
- Remove old painting using surface grinder.
- For best bond, concrete surface must be slightly textured.
- Allow it to dry before priming.
- Ensure that concrete must be cured at least 28 days and moisture content is below 5%.

○ Material Preparation

- Stir **HS Elastoseal Primer** thoroughly by using speed drill mixer with a spiral type of blade at the bottom of stirrer rod. The speed may be 450 – 600 rpm till homogeneous mix is obtained.
- After stirring, wait for the product to settle in order to let entrapped air escape.

○ Application of Material

- Apply **HS Elastoseal Primer** by brush / airless spray on cleaned surface.
- Once opened, drum should be used completely.

Health & Safety

- Avoid contact with skin / eyes and avoid swallowing.
- Ensure adequate ventilation and avoid inhalation of vapour.
- Wear suitable protective clothing, gloves and eye protection.
- In case of skin contact, rinse with plenty of clean water, then cleanse with soap and water. Do not use solvent to clean the contacted area.
- In case of eye contact, wash with plenty of clean water and seek medical advice.
- If swallowed, seek medical attention immediately. Do not induce vomiting.

Packing

Available in 20 L container

Storage

Store in a cool dry place, under shed, away from heat.

Shelf Life

6 months in original unopened sealed condition



SCIENTIFIC WATERPROOFING SOLUTIONS

DISCLAIMER

The information contained within this Data Sheet is based on information believed to be reliable at the time of its preparation. The Company will not be liable for loss or damage howsoever caused including liability for negligence, which may be suffered by the user of the data contained herein. It is the users' responsibility to conduct all necessary tests to confirm the suitability of any product or system for their intended use. No guarantee of results is implied since conditions of use are beyond our control.

BERGER PAINTS INDIA LIMITED
Berger House. 129, Park Street, Kolkata : 700 017
Phone : 91-33-2229-9724-28 / 6005-06, Fax : 91-33-2227-7288, 2249-9009/9729
e-mail : consumerfeedback@bergerindia.com ; Website : www.bergerpaints.com